

# Test Application Form

Report to:  Applicant/Supplier  Buyer Invoice to:  Applicant/Supplier  Buyer

Quotation No.: If available

Laboratory's Use Only:

Report No.:

Due Date:

**Applicant/Supplier:**

Applicant/Supplier Name:

Address:

Contact Person:

Telephone:

Cell:

E-Mail:

VAT-No Applicant:

**Payer:**

Payer Name:

Address:

Contact Person:

Telephone:

Cell:

E-Mail:

VAT-No Payer:

**Information Sample Material:**

Sample Description:

Composition:

Country of Destination:

Colour/Category:

End Use:

Style No.

Order No.

Article No.:

Country of Origin:

End Customer/Buyer:

Re-Test:  No  Yes, earlier report numberSelf-reference:  Yes  No

Others:

**Care Instructions:**

Washing:		Others:		Drycleaning:		Others:			
Bleaching:		Others:		Drying:		Others:		Ironing:	

**Tests Required:****Dimensional Stability:** Washing:  1 wash  3 washes**Dry Cleaning:** during steaming  during ironing**Appearance:** after washing:  1 wash  3 washes  after dry cleaning  
 wash and wear (easy/non ironing or self-smoothing)**Spirality/Twisting:** after washing:  1 wash  3 washes**Print Durability:** after washing:  1 wash  3 washes**Colour Fastness to:**

- Washing
- Water
- Dry cleaning
- Rubbing/crocking
- Perspiration
- Artificial light: Grade  4  5  6
- Sea water
- Swimming pool water
- Chlorine bleach
- Non-chlorine bleach
- Saliva and perspiration
- Phenolic yellowing
- Sublimation

**Physical:**

- Tensile strength *DIN EN ISO 13934*  -1 (Strip)  -2 (Grab)
- Tear strength *DIN EN ISO 13937*  
 -2 (Single tear)  -3 (Wing tear)  -4 (Tongue tear)
- Seam slippage *ISO 13936* -  1/  2
- Seam strength *ISO 13935* -  1/  2
- Bursting strength
- Abrasion resistance
- Water repellency
- Water absorption (capillary rise method)
- Attachment strength
- Moisture drying time
- Thread per inch/stitch density
- Yarn count
- Fabric weight
- Fibre composition
- Zipper strength
- Flammability
- Stretch & recovery (elongation)
- Care label recommendation/Verification
- Odour
- Corrosion resistance
- Visual assessments
- Pilling resistance:
  - ICI Pilling
  - Martindale
  - Random Tumble Pilling

**Chemical:**

- AZO dyes  Aniline
- pH value
- Formaldehyde
- Extractable heavy metals
- Heavy metals (Packaging materials)
- Chlorinated phenols PCP/TECP/OPP
- Allergenic & carcinogenic dyes
- Phthalates
- Organic tin compounds
- Chlorinated benzenes & toluene
- AP/APEO
- PFC
- PAH
- Release of nickel
- Total cadmium
- Total lead
- VOC
- PVC identification
- DMFu
- SCCP / MCCP
- Bisphenol  Bisphenol A
- Quinoline

**Test Packages:**

- OEKO-TEX® STANDARD 100  
OEKO-TEX® Product Class:  I  II  III  IV
- OEKO-TEX® Appendix:  4  6
- PPC

Others:

**Service Type:** (Special services are only available for certain tests. Nickel release test takes 7-10 days by nature of testing.) Regular (4 Working Days)  Express (3 Working Days - 40% Surcharge)  Emergency (2 Working Days - 100% Surcharge)  Same Day (150% Surcharge)

We request for the above tests &amp; agree that all testing will be carried out subject to Hohenstein scale of charges as set forth in their price list of which we have seen a copy.

Date

Authorized Signature or Company Stamp